

Application/Control Number: 10/828,864

Art Unit: 3724

page 2 of 13

In the claims:

Please amend the claims as follows:

1. (original) A plastic pipe cutting device comprising:

a top sleeve, said top sleeve having a semi-circular cross section, said top sleeve having an exterior, said top sleeve having an interior;

a bottom sleeve hingedly connected to said top sleeve, said bottom sleeve having a semi-circular cross section, said bottom sleeve having an exterior, said bottom sleeve having an interior, said bottom sleeve capable of being brought adjacent to said top sleeve;

a top guide track connected to said top sleeve exterior, said top guide track coaxial to said top sleeve, said top guide track having a T-shaped cross section;

a bottom guide track connected to said bottom sleeve exterior, said bottom guide track coaxial to said bottom sleeve, said bottom guide track having a T-shaped cross section, said bottom guide track and said top guide track forming a continuous track when said bottom sleeve is brought adjacent to said top sleeve;

a roller housing;

a guide roller rotatably connected to said roller housing, said guide roller capable of rolling upon said top guide track, said guide roller capable of rolling upon said bottom guide track;

a blade connected to said roller housing, said blade capable of cutting a plastic pipe; and

a rasp connected to said roller housing, said rasp capable of filing the end of a plastic pipe.

Application/Control Number: 10/828,864

Art Unit: 3724

page 3 of 13

2. (original) The plastic pipe cutting device of claim 1 further comprising:
at least one top rubber grip connected to said top sleeve interior; and
at least one bottom rubber grip connected to said bottom sleeve interior.

- 5 3. (original) The plastic pipe cutting device of claim 1 further comprising:
a clasp connected to said bottom sleeve, said clasp capable of securing
said top sleeve to said bottom sleeve.

- 10 4. (original) The plastic pipe cutting device of claim 1 further comprising:
a platform slidably connected to said roller housing.

5. (original) The plastic pipe cutting device of claim 4 wherein:
said blade is connected to said platform.

- 15 6. (original) The plastic pipe cutting device of claim 4 wherein:
said rasp is connected to said platform.

7. (original) The plastic pipe cutting device of claim 1 further comprising:
a tension adjuster threadably connected to said roller housing.

20

8. (original) The plastic pipe cutting device of claim 7 further comprising:
a handle connected to said tension adjuster.

Application/Control Number: 10/828,864

Art Unit: 3724

page 4 of 13

9. (original) The plastic pipe cutting device of claim 1 further comprising:
a hinge connected to said top sleeve, said hinge connected to said bottom sleeve.

5 10. (original) The plastic pipe cutting device of claim 1 wherein:
said top guide track and said bottom guide track are comprised of steel.

11. (canceled) A plastic pipe cutting device comprising:
a top sleeve, said top sleeve having a semi-circular cross section, said top sleeve having an exterior, said top sleeve having an interior;
10 at least one top rubber grip connected to said top sleeve interior;
a bottom sleeve hingedly connected to said top sleeve, said bottom sleeve having a semi-circular cross section, said bottom sleeve having an exterior, said bottom sleeve having an interior, said bottom sleeve capable of being brought
15 adjacent to said top sleeve;
at least one bottom rubber grip connected to said bottom sleeve interior;
a top guide track connected to said top sleeve exterior, said top guide track coaxial to said top sleeve, said top guide track having a T-shaped cross section;
a bottom guide track connected to said bottom sleeve exterior, said bottom
20 guide track coaxial to said bottom sleeve, said bottom guide track having a T-shaped cross section, said bottom guide track and said top guide track forming a continuous track when said bottom sleeve is brought adjacent to said top sleeve;
a roller housing;

Application/Control Number: 10/828,864

Art Unit: 3724

page 5 of 13

a guide roller rotatably connected to said roller housing, said guide roller capable of rolling upon said top guide track, said guide roller capable of rolling upon said bottom guide track;

a blade connected to said roller housing, said blade capable of cutting a plastic pipe; and

a rasp connected to said roller housing, said rasp capable of filing the end of a plastic pipe.

12. (amended) A plastic pipe cutting device comprising:

a top sleeve, said top sleeve having a semi-circular cross section, said top sleeve having an exterior, said top sleeve having an interior;

at least one top rubber grip connected to said top sleeve interior;

a bottom sleeve hingedly connected to said top sleeve, said bottom sleeve having a semi-circular cross section, said bottom sleeve having an exterior, said bottom sleeve having an interior, said bottom sleeve capable of being brought adjacent to said top sleeve;

at least one bottom rubber grip connected to said bottom sleeve interior;

a top guide track connected to said top sleeve exterior, said top guide track coaxial to said top sleeve, said top guide track having a T-shaped cross section;

a bottom guide track connected to said bottom sleeve exterior, said bottom guide track coaxial to said bottom sleeve, said bottom guide track having a T-shaped cross section, said bottom guide track and said top guide track forming a continuous track when said bottom sleeve is brought adjacent to said top sleeve;

Application/Control Number: 10/828,864

Art Unit: 3724

page 6 of 13

a roller housing;

a guide roller rotatably connected to said roller housing, said guide roller
capable of rolling upon said top guide track, said guide roller capable of rolling
upon said bottom guide track;

5 a blade connected to said roller housing, said blade capable of cutting a
plastic pipe; and

a rasp connected to said roller housing, said rasp capable of filing the end
of a plastic pipe; and

~~The plastic pipe cutting device of claim 11 further comprising:~~

10 a clasp connected to said bottom sleeve, said clasp capable of securing
said top sleeve to said bottom sleeve.

13. (original) The plastic pipe cutting device of claim 12 further comprising:
a platform slidably connected to said roller housing.

15

14. (original) The plastic pipe cutting device of claim 13 wherein:
said blade is connected to said platform.

15. (original) The plastic pipe cutting device of claim 14 wherein:
20 said rasp is connected to said platform.

16. (original) The plastic pipe cutting device of claim 15 further comprising:
a tension adjuster threadably connected to said roller housing.

Application/Control Number: 10/828,864

Art Unit: 3724

page 7 of 13

17. (original) The plastic pipe cutting device of claim 16 further comprising:
a handle connected to said tension adjuster.

5 18. (original) The plastic pipe cutting device of claim 17 further comprising:
a hinge connected to said top sleeve, said hinge connected to said bottom
sleeve.

10 19. (original) The plastic pipe cutting device of claim 18 wherein:
said top guide track and said bottom guide track are comprised of steel.

20. (original) A plastic pipe cutting device comprising:
a top sleeve, said top sleeve having a semi-circular cross section, said top
sleeve having an exterior, said top sleeve having an interior;
15 at least one top rubber grip connected to said top sleeve interior;
a bottom sleeve hingedly connected to said top sleeve, said bottom sleeve
having a semi-circular cross section, said bottom sleeve having an exterior, said
bottom sleeve having an interior, said bottom sleeve capable of being brought
adjacent to said top sleeve;
20 at least one bottom rubber grip connected to said bottom sleeve interior;
a steel top guide track connected to said top sleeve exterior, said top guide
track coaxial to said top sleeve, said top guide track having a T-shaped cross
section;

Application/Control Number: 10/828,864

Art Unit: 3724

page 8 of 13

a steel bottom guide track connected to said bottom sleeve exterior, said bottom guide track coaxial to said bottom sleeve, said bottom guide track having a T-shaped cross section, said bottom guide track and said top guide track forming a continuous track when said bottom sleeve is brought adjacent to said top sleeve;

5 a roller housing;

a guide roller rotatably connected to said roller housing, said guide roller capable of rolling upon said top guide track, said guide roller capable of rolling upon said bottom guide track;

a platform slidably connected to said roller housing;

10 a blade connected to said roller housing, said blade capable of cutting a plastic pipe, said blade connected to said platform;

a rasp connected to said roller housing, said rasp capable of filing the end of a plastic pipe, said rasp connected to said platform;

15 a clasp connected to said bottom sleeve, said clasp capable of securing said top sleeve to said bottom sleeve;

a tension adjuster threadably connected to said roller housing;

a handle connected to said tension adjuster; and

a hinge connected to said top sleeve, said hinge connected to said bottom sleeve.

20